



**MARCH 2010**

For easy specifying/product detailing, copy and paste the text below. Delete irrelevant detail where indicated.

## **Draft Specification**

### **Product name:**

ModWood

### **Profile:**

Mini Board 68 x 17 mm

Solid Decking 88 x 23 mm

Wide Decking 137 x 23 mm

Marina Board 137 x 32 mm

### **Colour:**

Black Bean

Jarrah

Sahara

Silver Gum

### **Finish:**

Brushed

Smooth

### **Fixing:**

Installation to be in accordance with ModWood's specifications (refer to web site) and relevant building codes. If using Kleva Klip please refer to Kleva Klip's fixing instructions, [www.klevaklip.com.au](http://www.klevaklip.com.au)

As ModWood expands in heat and sun, to avoid building stress into the boards and having possible lengthways shrinkage, it is best to fix the boards when the ambient temperature is less than 25°C and when the boards are not sitting in full sun (see "coefficient of thermal linear expansion" on our web site).

### **Storage & Handling:**

ModWood packs should be stored in a dry, flat area under roof and off the ground. Loose boards should be stored on its edge in a dry, flat area under roof and off the ground. Failure to keep packs dry in storage can lead to the growth of mould spores on boards. When moving product, ModWood should be carried on its edge.

Please note ModWood is a finished product – take care.

### **Manufacturer:**

ModWood Technologies Pty Ltd

Ph: 03 9357 8866

Email: [info@modwood.com.au](mailto:info@modwood.com.au)

Website: [www.modwood.com.au](http://www.modwood.com.au)